

HAFSTalpha - Semiautomatic color controller

CONTROL INDIVIDUAL LIGHT GROUPS VIA A TOUCHSCREEN

















The HAFSTalpha is the latest generation of semiautomatic color controllers from OLIGO Lichttechnik GmbH – surface controls. Light scenarios and light groups can be quickly and conveniently configured via a TFT touchscreen display. A large overview display of the color matching booth visualizes the settings that have been made.

The HAFSTalpha is used in: color matching booths, color matching tabletop booths, color matching light laboratories







Features Display

15.6" Full-HD TFT display

With fully integrated touchscreen

Interfaces 2 x Ethernet 10/100/1000

Outputs • 6 DALI output modules

> Control of up to 192 LEDCCO; 128 LEDCCO B3; 192 LEDMRO

Inputs

Technical specifications

Permitted ambient 41°F - 95°F (+5°C to +35°C)

temperature

Supply voltage Controller: 24 V DC

Junction box: 100-240 V AC

Power consumption 50 watt

50-60 Hz Frequency

Degree of protection • Controller: IP65

Junction box: IP54

Protection class

Exterior and mounting dimensions of the HAFSTalpha. All data in Inch (mm).

System components

- Semiautomatic color controller
- Junction box of the controller
- Support arm system

Optional accessory

Radio remote control

Special information

- Easy and convenient to operate
- Selection of various menu languages
- Optional: Scene selection possible via mobile device

Quality criteria

- PWIS-free
- UL certified components
- Protected against shortcircuits and overload

Order number	Type code	System components	Dimensions in mm (WxHxD)	Housing material	Weight in kg
M308HA001AZ-EN	HAFST <i>alpha</i> us	Semiautomatic color controller with touchscreen	17,00" x 12,20" x 2,95" 432 x 309 x 125	Aluminum, Painting: white aluminum (similar to RAL9006)	approx. 5.3
		incl. junction box of the controller	15,75" x 15,75" x 4,72" (400 x 400 x 120)	Steel sheet, RAL7035 powder coated	approx. 8.5
		incl. support arm system			

www.surface-controls.com

